


Laminated Architectural Shingle


















TEST COMPLIANCE

- · ASTM D7158 Class H
- ASTM D3462
- ASTM D3161 Class F
- ASTM D3018 Type I
- ASTM E108 Class A Fire Rating
- CSA A123.5
- ICC Approval ESR 3150
- FBC Approval #14809

DISCLAIMER: Sample pieces or photographs of shingles may not accurately represent the true color or variations of color blends that will appear on the roof. Before installation, five or six shingles should be laid out and reviewed for conformity to desired color level. If color levels are unsatisfactory, advise your dealer before proceeding with installation. Colors and specifications subject to change without notice. Shingle colors not available in all regions. Limited warranties carry terms and conditions. Please contact your local Malarkey representative for color availability and further information. See Malarkey's Shingle and Accessory Warranty for details. For complete Limited Lifetime Warranty details, reference Malarkey's Shingle and Accessory Warranty.

*Malarkey shingles featuring Scotchgard™ Protector must be installed with EZ-Ridge™ (8", 10") or RidgeFlex™ (10", 12") hip and ridge products, which feature Scotchgard™ Protector, to receive Malarkey's full 20-year Algae Resistant Shingle warranty. The Alaskan® featuring Scotchgard™ Protector can be substituted as hip and ridge shingles, in conjunction with Malarkey shingles featuring Scotchgard™ Protector, to receive the full Malarkey 20-year Algae Resistant Shingle warranty. Scotchgard and the Scotchgard logo, including the plaid design and 3M logo, are all trademarks of 3M.

**Some contractors adopt roofing shingles to use as hip and ridge shingles. Use of The Alaskan® as a hip and ridge shingle will apply towards the Enhanced Wind Warranty. Dura-Seal™ shingles used for hip and ridge will not qualify toward an Enhanced Wind Warranty. This version supersedes all previous versions. Rev. 1/16





DOUBLE RAIN SEAL PROTECTION

A rain seal helps hold shingles in place during high winds and protects against wind-blown rain entering beneath the shingles. Malarkey laminate shingles are manufactured with an extra line of defense in the critical area for laminated shingles, with double SEBS asphalt rain seals. Malarkey's SEBS asphalt has adhesive properties to join the shingle together and cohesive properties to prevent it from separating. SEBS is also flexible down to 0°F (-18°C), ensuring the rain seal remains intact through freeze and thaw cycles.

SCOTCHGARD™ PROTECTION FROM 3M

SUPERIOR GRANULAR EMBEDMENT Malarkey's quality control combined with exceptional materials ensures superior granule adhesion and durability to protect your investment.

One of the most critical aspects of a successful roofing project is correct installation. Improper fastener placement is the leading cause of incorrect shingle installation and can subsequently void the warranty. Malarkey laminate shingles are manufactured with The Zone® patented nailing area, which is over three times larger than other laminate shingles and dramatically improves correct fastener placement.

Algae growth on a roof can cause black streaks, which can alter the color of your roof and make it appear aged. Shingles with Scotchgard $^{\!{\scriptscriptstyle \mathsf{TM}}}$ Protector help maintain the aesthetic appearance of your roof by resisting black streaks caused by algae, which may reduce the need to clean your roof. Shingles with Scotchgard™ Protector include a





20-year warranty.

THE ZONE®





WARRANTY



LIMITED WIND WARRANTY

Northwest-XL $^{\!\scriptscriptstyle{\text{TM}}}$ shingles come with a 110 mph (177 kph) Limited Wind Warranty.

ENHANCED WIND WARRANTY

Northwest-XL[™] shingles are eligible for a 130 mph (209 kph) Enhanced Wind Warranty when Malarkey's Smart Start™ shingles are installed, shingles are 6-nailed, and either of Malarkey's hip and ridge shingles -EZ-Ridge[™] (8", 10") or RidgeFlex[™] (10", 12") – are used. Malarkey's performance-driven underlayments – Arctic Seal®, Right Start™ UDL, or SecureStart[™] – are recommended for added system protection.

FEATURING

- · Limited Lifetime Shingle Warranty
- 12-year Right Start[™] Warranty

LISTED
_





Northwest-XL™

Antique Brown	Black Oak	Heather	Midnight Black	Natural Wood	Silverwood	Storm Grey	Weathered Woo
•	•	•	•	•	•	•	

Distributed from: • Portland, OR



P.O. BOX 17217, Portland, OR 97217 503.283.1191 | 800.545.1191 | Fax: 503.289.7644

WWW.MALARKEYROOFING.COM